

POSITION SWITCH, METAL-ENCLOSED DEGREE OF PROTECTION IP67  
SNAP-ACTION CONTACTS, ROLLER CRANK, ADJUSTABLE LENGTH 1 X M20  
X 1,5



|                                                          |  |                                |                      |
|----------------------------------------------------------|--|--------------------------------|----------------------|
| product designation                                      |  | position switch                |                      |
| General technical data                                   |  |                                |                      |
| protection class IP                                      |  | IP67                           |                      |
| reference code according to IEC 81346-2                  |  | B                              |                      |
| active principle                                         |  | mechanical                     |                      |
| Substance Prohibittance (day/month/year)                 |  | 07/01/2006                     |                      |
| Net Weight                                               |  | 0.312 kg                       |                      |
| length of the sensor                                     |  | 182.5 mm                       |                      |
| width of the sensor                                      |  | 40 mm                          |                      |
| Ambient conditions                                       |  |                                |                      |
| ambient temperature                                      |  | -30 ... +85 °C                 |                      |
| ● during operation                                       |  |                                |                      |
| explosion protection category for dust                   |  | none                           |                      |
| design of the switching contact                          |  | mechanical                     |                      |
| number of NC contacts for auxiliary contacts             |  | 1                              |                      |
| number of NO contacts for auxiliary contacts             |  | 1                              |                      |
| Enclosure                                                |  |                                |                      |
| design of the housing                                    |  | design complying with EN 50041 |                      |
| material of the enclosure                                |  | metal                          |                      |
| coating of the enclosure                                 |  | painted                        |                      |
| design of the housing according to standard              |  | Yes                            |                      |
| Drive Head                                               |  |                                |                      |
| design of the actuating element                          |  | twist lever, adjustable length |                      |
| design of the switching function                         |  | CO contact                     |                      |
| circuit principle                                        |  | snap-action contacts           |                      |
| number of switching contacts safety-related              |  | 1                              |                      |
| Installation/ mounting/ dimensions                       |  |                                |                      |
| fastening method                                         |  | screw fixing                   |                      |
| Connections/ Terminals                                   |  |                                |                      |
| type of electrical connection                            |  | screw terminal                 |                      |
| design of the interface for safety-related communication |  | without                        |                      |
| Communication/ Protocol                                  |  |                                |                      |
| design of the interface                                  |  | without                        |                      |
| Approvals Certificates                                   |  |                                |                      |
| General Product Approval                                 |  | Test Certificates              | Maritime application |
|                                                          |  |                                | other                |



Miscellaneous



Confirmation



## Environment

[Environmental Confirmations](#)

## Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SE2120-1UW>

Cax online generator


<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SE2120-1UW>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SE2120-1UW>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SE2120-1UW&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SE2120-1UW&lang=en)



last modified:

8/8/2025